



限りある資源と美しい自然を大切に

## MODEL SC-2515

# NOTCHING MACHINE

### Outline

The SC-2515 notching machine makes a predetermined notch in a test piece for impact testing of hard plastic. The safety acrylic cover provides safety measures during driving and prevents cutting chips from scattering. The notch shape can be V-shaped or U-shaped by changing the cutter shape. You can also use other suitable cutters to perform cutting other than notches.



MODEL SC-2515



株式会社 上島製作所

UESHIMA SEISAKUSHO CO., LTD

## Feature

O Notch shape (cutter blade shape) can be selected from V-shaped and U-shaped.

O By changing the cutter, it is possible to perform cutting processes other than notches.

## Specification

MODEL		SC-2515
Applicable Standard (*1)	For Izod tests	JIS K7110-1999, ISO 180
	For Charpy tests	JIS K7111-1-2012, ISO 179
Cutter Speed		Approx. 900 rpm at full load, (1000 rpm at no load)
Applicable Cutter		Selection of V-shaped and U-shaped cutters (Specify number of blades, tip angle and radius.)
Sample Table Up/Down Stroke		20 mm
Sample Table Sliding Stroke		40 mm
Clampable Sample Size (* JIS sample size is just for reference)		Length: 60 to 120 mm Width: 1 to 25 mm Thickness: 1 to 15 mm (JIS sample size in mm: L=80±2, W=10.0±0.2, t=4.0±0.2)
Motor		200W
Power Supply Required		100VAC, 50/60Hz, 15A
Dimensions & Weight		Approx. 395 mm(W) x 410 mm(D) x 310 mm(H) Approx. 43kg
Safety Measures		Safety cover (stops the motor when opened) Motor stops in case of motor abnormality Emergency stop switch Leakage current breaker

(\*1) Notch processing of type 1 test piece of JIS K7160-1996 is also possible using a cutter complying to this standard.

UESHIMA SEISAKUSHO CO., LTD.

<Manufacturer>

# Ueshima

**UESHIMA SEISAKUSHO CO., LTD.**

6-5-22, Yaho, Kunitachi-shi, Tokyo 186-0011, Japan

TEL.81-42-572-1397 FAX.81-42-573-1520

E-mail:sales@ueshima-seisakusho.com

<http://www.ueshima-seisakusho.com>